



**Østeragade 65**

**9560 Hadsund**

**Telefon 70 70 7639**

**[www.jenslubeck.dk](http://www.jenslubeck.dk)**

**[info@jenslubeck.dk](mailto:info@jenslubeck.dk)**

**2023**



# PROFESSIONALISM IN EVERY FIELD



[uniamachines.com](http://uniamachines.com)



# APOLLO PREMIUM

SPREADER  
WITH WIDE ADAPTER

**Good load capacity and manoeuvrability** – thanks to large wheels that provide less rolling resistance.

**Liquid-tightness and comfort** – thanks to the tubular construction of the hopper.

**Mining grade conveyor chain links** – with a diameter of 14 mm to ensure durability and long service life.

**The large wheels of the spreader** – protect the soil structure and make it easier to manoeuvre and pass even in difficult working conditions.

**Reduced load on the tractor hitch** – even on uneven ground. This is provided by a longitudinal leaf spring located in the drawbar line.

**A wide range of capacities** – capacities up to 16 tonnes allow the spreader to be configured according to the needs of the farm.

**Various control options of the floor conveyor available** – via standard potentiometer or with one of 3 optional controllers: Spread, Starter Spread, Starter Spread Pro or SUPERIOR.

**Extensive standard equipment** – hydraulic tailgate, mechanical drawbar support, lighting system and air brake system.

**ISOBUS compatibility** – allows operation in precision farming standards in APOLLO 11-16 PREMIUM models (option).

	MODEL	APOLLO 8 PREMIUM	APOLLO 10 PREMIUM	APOLLO 11 PREMIUM	APOLLO 13 PREMIUM	APOLLO 14 PREMIUM	APOLLO 16 PREMIUM
Load capacity [kg]	Nominal	6,500	8,000	9,000	10,000	11,000	13,000
	On the field	9,000	11,000	12,000	13,000	14,000	16,000
Adapter width [m]		1.8	1.8	2.0	2.0	2.0	2.0
PTO speed [rpm]		540	540	540	540	1,000	1,000
Working width [m]	Vertical 2-shaft adapter	8÷12	8÷12	8÷12	8÷12	8÷12	8÷12
	Horizontal/Shredder adapter	12÷24	12÷24	12÷24	12÷24	12÷24	12÷24
Standard tyres		18.4-34	18.4-38	23.1 R26	580/70 R38	28.1 R26	650/70 R32



# TYTAN 20 / 24

SPREADER  
EFFICIENT  
AND ROBUST

**Comfort and safety during work and transport** – thanks to the longitudinal leaf spring located in the drawbar line.

**Axles with follow-up control** – allow the wheels of the spreader to turn in line with the tractor's direction of travel when cornering.

**Good weight distribution** – through the use of two-axle spring suspension. This optimises the drawbar pressure on the hitch.

**Minimal soil compaction** – thanks to large wheel contact area.

**Simplified operator work** – thanks to convenient, stepless adjustment of the floor conveyor.

**Four-chain conveyor (2 pairs) with 14 mm link diameter** – ensures durability and a long service life.

**Large number of options** – the spreader can be equipped with one of three optional controllers and three different types of adaptor (2-shaft vertical, 2-shaft horizontal, shredder), or with a capacity attachment.

**Extensive standard equipment** – hydraulic tailgate, rear adapter cover, air brake system, road lights, drawbar support.

**ISOBUS compatibility** – allows operation in precision farming standards (option).

MODEL	TYTAN 20	TYTAN 24	
Load capacity [kg]	Nominal	14,000	18,000
	On the field	16,000	20,000
Adapter width [m]	2.0	2.0	
PTO speed [rpm]	1,000	1,000	
Working width [m]	Vertical 2-shaft adapter	8÷12	8÷12
	Horizontal/Shredder adapter	12÷24	12÷24
Standard tyres	550/60-22.5	600/55-26.5	



# TYTAN 30 / 36

THREE-AXLE  
SPREADER

**Good weight distribution of the machine** – through the use of a three-axle chassis. This reduces the drawbar pressure on the hitch and allows the use of capacity hoppers.

**Impressive load capacity** – can reach up to 24 t. The spreader is ideal for large-scale farms.

**Safe and trouble-free operation** – thanks to the liquid-tight, tubular body construction and robust chassis.

**Working and transport comfort** – thanks to the longitudinal leaf spring located in the drawbar line, which provides excellent vibration damping.

**Special gearbox for high loads** – supported by a hydraulic floor conveyor drive.

**High quality, long service life** – thanks to the manufacturing of the key working elements of the adapter from top-quality HARDOX steel.

**Large number of options** – the spreader can be equipped with one of three optional controllers and different types of adaptor: 2-shaft vertical, 2-shaft horizontal (TYTAN 30), 3-shaft horizontal (TYTAN 36), shredder or with a capacity attachment.

**Extensive standard equipment** – hydraulic tailgate, rear adapter cover, air brake system, road lights, drawbar support.

**ISOBUS compatibility** – allows operation in precision farming standards (option).

MODEL	TYTAN 30	TYTAN 36	
Load capacity [kg]	Nominal	20,000	22,000
	On the field	22,000	24,000
Adapter width [m]	2.0	2.25	
PTO speed [rpm]	1,000	1,000	
Working width [m]	Vertical 2-shaft adapter	8÷12	8÷12
	Horizontal/Shredder adapter	12÷24	12÷24
Standard tyres	550/60-22.5	600/55-26.5	



**Kontakt:**

**Østergade 65  
9560 Hadsund**

**Telefon 70 70 7639**

**[info@jenslubeck.dk](mailto:info@jenslubeck.dk)**

