



**Østeragade 65**

**9560 Hadsund**

**Telefon 70 70 7639**

**[www.jenslubeck.dk](http://www.jenslubeck.dk)**

**[info@jenslubeck.dk](mailto:info@jenslubeck.dk)**

**2023**



# PROFESSIONALISM IN EVERY FIELD



[uniamachines.com](http://uniamachines.com)



# TOP

FRONT TANK

**Transport convenience** – the two front position lamps have direction indicators. The tank also has a set of transport wheels for rolling.

**Two pumps with different max. flow rates available** – version H LUX: 85 l/min., version E LUX: 19 l/min.

**Two rotary washers** – H LUX and E LUX versions.

**Efficient tank** – made of polyethylene with a capacity of 1,350 litres. Has a suction filter.

**Health and safety** – the hand wash tank has a capacity of 25 litres.

MODEL	TOP 1200 H LUX	TOP 1200 E LUX	TOP 1200 H
Hopper capacity [l]	1,350	1,350	1,350
Control	hydraulic (1 pair of hoses)	electrical (3-pin, 12 V power socket)	hydraulic (1 pair of hoses)
Pump capacity	85 l/min.	19 l/min.	85 l/min.
Transport dimensions: L/W/H [m].	1.8 / 2.1 / 1.4	1.8 / 2.1 / 1.3	1.8 / 2.1 / 1.3
Weight [kg]	320	285	300



# LUX

## MOUNTED SPRAYER

**Simple and convenient operation** – thanks to the hydraulically controlled boom, which rises to a height of 2.1 metres.

**Practical three-section tank** – shaped to ensure that it can be completely emptied on any terrain.

**Independent boom** – makes it possible to avoid obstacles in the field or its border (optional).

**Convenient cleaning of the inside of the tank** – thanks to a rotary washer for rinsing the tank after spraying is completed.

**Robust liquid system** – made of acid-resistant tubing.

**Easy-to-operate constant pressure valve** – with pressure compensation.

**Expandable with a solenoid valve and SPRAY control computer** – so that the correct spray rate is maintained regardless of driving speed (optional).

**Extensive standard equipment** – including: sectional filters, 5 working sections, diluter in the main tank filler, and hand wash tank.

MODEL	LUX
Hopper capacity [l]	600 / 800 / 1,000
Working width [m]	15
Number of sections	5
Boom lifting range [m]	0.5÷1.7/0.5÷2.1
Pump [capacity]	ZETA 100 [100 l/min.] / ZETA 140 [140 l/min.]*

\* Applicable to models with 800 and 1,000 litre tanks



# EUROPA

## TRAILED SPRAYER

**Medium and large trailed sprayers**  
– with hydraulically controlled, independent boom.

**Tanks with capacities of 2,500, 3,000 and 4,000 litres** – made of polyester, with two breakwaters to limit internal liquid movement.

**Reduction in vibrations and unwanted boom movements** – thanks to pendulum stabilisation with shock absorbers.

**Safe preparation of the spray liquid** – by using a standard 40-litre side diluter (60-litre diluter available as an option).

**Convenient operation of the liquid system from the tractor cab** – thanks to the SPRAY control computer, which is standard equipment on the machine (RADION computer available as an option).

**The machine can be controlled via ISOBUS and the TOUCH terminal** – this allows a range of additional precision farming options to be introduced to the farm (optional).

**Adjustable wheelbase (1.80 – 2.25 m) and a wide range of tyre options** – versatile use of the machine in a variety of crops.

**A wide range of optional equipment to adapt the machine to individual needs** – possible features such as navigation with automatic section control, DYSTANS CONTROL system, tracking drawbar, liquid circulation in the boom, or pneumatic axle suspension.

MODEL	EUROPA XL
Hopper capacity [l]	2,500 / 3,000 / 4,000
Working width [m]	21 / 24 / 27 / 28
Number of sections	5÷13
Boom lifting range [m]	0.5÷2.3
Pump [capacity]	POLY 2300 [300 l/min.]



# EGRET

## TRAILED SPRAYER

**The robust construction and compact body of the sprayer** – makes the machine compact and safe to drive.

**High-capacity spray tank** – made of polyester, with two breakwaters to limit the movement of the liquid.

**Stable independent boom as standard** – with shock absorbers that effectively absorb any vibrations and unwanted movements during operation.

**Easy and intuitive operation of the sprayer** – thanks to ergonomically arranged and clearly labelled valves.

**Convenient operation of the liquid system from the tractor cab** – thanks to the SPRAY control computer, which is standard equipment on the machine (RADION computer available as an option).

**Option to equip the sprayer with a precision farming package** – parallel driving and automatic section control (optional).

**Versatile use of the machine in various crops** – thanks to an adjustable wheelbase (1.50 – 1.80 m) and various wheel size options to choose from.

**A range of optional extras to choose from to adapt the machine's configuration to individual needs** – such as a larger 60-litre diluter, tracking drawbar, mechanical axle suspension, or boom night lights.

MODEL	EGRET
Hopper capacity [l]	2,000 / 2,500 / 3,000
Working width [m]	18 / 20 / 21
Number of sections	5÷9
Boom lifting range [m]	0.5÷2.3
Pump [capacity]	ZETA 260 [260 l/min.]



# HERON

TRAILED  
SPRAYER

**Large trailed sprayers dedicated to larger farms** – with hydraulically controlled, independent boom.

**Tanks with capacities: 4,200 and 5,000 litres**

– made of polyester, with breakwaters to limit the movement of the liquid inside the tank.

**Reduction in vibrations and unwanted boom movements** – thanks to pendulum stabilisation with shock absorbers.

**Safe preparation of the spray liquid** – by using a standard side diluter with a high capacity of up to 60 litres.

**Conveniently located control valves** – concealed under a hinged cover that protects them from contamination during spraying in difficult field conditions.

**Convenient operation of the liquid system** – thanks to standard RADION control computer (ISOBUS control available as an option).

**Individual choice of drive axle** – rigid with adjustable wheelbase (1.80 – 2.25 m), or steering axle (2.00 or 2.25 m).

**Extensive standard equipment** – pneumatic axle suspension, boom night light, hydraulic support foot, sectional filters, tank filling connection, and shock-absorbing drawbar.

**A range of optional equipment options to choose from** – solutions and systems, such as navigation with automatic section control, V-SYSTEM, DYSTANS CONTROL, EDS (where each head is a separate working section), or an autonomous hydraulic system.

MODEL	HERON
Hopper capacity [l]	4,200 / 5,000
Working width [m]	21 / 24 / 27 / 28 / 30
Number of sections	5÷13
Boom lifting range [m]	0.5÷2.3
Pump [capacity]	POLY 2300 [300 l/min.]



**Kontakt:**

**Østergade 65  
9560 Hadsund**

**Telefon 70 70 7639**

**[info@jenslubeck.dk](mailto:info@jenslubeck.dk)**

