



Østeragade 65 9560 Hadsund Telefon 70 70 7639 www.jenslubeck.dk info@jenslubeck.dk

2023









Free flow of even poorly cut straw – ensured by the large clearance between the working elements. The tine spacing is 41 cm and the spacing between the tines in a single row is 82 cm.

Two-stage adjustment of KX tines – one step reduces the rake angle of the tine and allows shallow work with full undercut. The second proves useful when there is a problem with the machine digging in. The chisel is set at an aggressive angle.

Full undercut even in shallow work – thanks to the special arrangement. The width of the undercutter is 440 mm, which is 3 cm wider than the tine pitch, allowing the operation of partially worn coulters.

Digging in even in very dry conditions – made possible by the individual pressure on the tine coulter (320 kg) and one of two adjustment stages.

Works with older tractors with low lifting capacity of the three-point hitch – KOS H 6 is equipped with a chassis. The axle has air brakes as standard.

Optional extras – the optional harrow B with two rows of AGRESSIVE Ø 460 mm discs completes the work of the tines by mixing straw with the topsoil.

TECHNICAL DATA	KOS B / S				KOS B H / S H			
	2.1	2.6	3	3.7	3.7	4.5	5.4	6
Weight with bolt protection option (KOS B) [kg]	720	800	915	1,270	1,830	2,080	2,375	2,530
Weight with spring protection option (KOS S) [kg]	930	1,050	1,200	1,650	2,360	2,560	2,950	3,080
Power requirement with bolt protection option (KOS B) [HP]	65÷80	80÷100	100÷140	140÷160	130÷160	140÷190	160÷200	200÷260
Power requirement with spring protection option (KOS B) [HP]	75÷100	90÷120	115÷150	140÷180	150÷190	170÷220	190÷260	190÷260
Number of tines [pcs]	5	6	7	9	9	11	13	13



Kontakt:

Østergade 65 9560 Hadsund

Telefon 70 70 7639

info@jenslubeck.dk







